

PA-3

Proper
Audio GmbH



Full Range Cabinet

The PA-3 gives Hi-Fi grade audio in a robust cabinet with a tough structural paint finish. The PA-3 feels at home in both mobile and installation applications. This cabinet will amaze you with its clarity and definition. The PA-3 is designed with a small footprint, best suited for commercial installation projects that require highest audio quality with minimal visual impact. The PA-3 is equipped with a 3" full range driver and offers 70° conical dispersion. The internal passive filter network of the standard version ensures a usable frequency response of 125 Hz to 18 kHz and a maximum SPL of 110 dB (peak) without the need for additional processing, while the A-version relies on external DSP for even smoother frequency and phase response. The discreet and 'retro' look makes the PA-3 fit any style of décor.



Mounting options include integrated M6 fixing points (two per side) for use with the included cradle or optional mic stand and mini spigot adapter that will allow using readily available 3/8" hardware. The rear connector plate offers 2x Neutrik NL4 connectors fitted as standard while the install version comes with 2 metres of pre-installed 2x 1,5 mm² loudspeaker cable for easy installation. When mounting to a wall or ceiling, the cable can be fed through the middle hole in the cradle, allowing neat and tidy cable management. Custom colours are available on request to make the appearance even more seamless with the surroundings or adopt your CD/CI.

Use in conjunction with PA-8B or PA-12B subwoofers to extend the usable frequency range to below 40 Hz.

Technical Specifications

Design	1x 3" mid/high cabinet	Closed box
Impedance	16 Ohms (nominal)	
Power Handling	20 / 40 / 80 W	AES / program / peak 10 ms
Sensitivity	91 dB	1 W / 1 m
Max SPL	104 / 110 dB	cont. / peak
Frequency Response	125 Hz – 18 kHz	-6 dB
Dispersion	70° conical	
Crossover	120 Hz HPF BW18	Mandatory for operation under full power!
Connectors	2x Neutrik NL4	Optional: permanently attached cable (I)
Dimensions	125 x 125 x 130 mm	H x W x D without cradle and screws
Weight	1.5 kg	
Colour	black / white (W) as standard	RAL colours (C) on request
Rigging	U-bracket (standard)	4x M6 mounting points

Order Codes and suffixes

PA-3	Mobile (NL4) version including U-bracket, all black, passive filter
I	Installation version with permanently installed cable
A	A-Version without passive filter
W	white cabinet, white U-bracket
Cxxxx	custom colour (xxxx = RAL number)

Example: PA-3AIC5017 – A-Version with permanently attached cable, traffic blue RAL 5017



All our products are handmade in Germany by a bunch of crazy audio nerds.

Proper Audio GmbH
Grevenbroicher Str. 8
41363 Jüchen
Germany

www.proper-audio.de
sales@proper-audio.de
+49 (0)2181 - 495300